INDEX	OF SHEETS	
SHEET NO.	SHEET DESCRIPTION	SHEET TITLE
1	CV01	COVER SHEET
2	NT01	NOTES
3	EX01	EXISTING CONDITIONS & DEMOLITION PLAN
4	SP01	OVERALL SITE PLAN AND SIGNAGE PLAN
5	0U01	OVERALL UTILITY PLAN
6	EC01	INITIAL EROSION CONTROL
7	EC02	INITIAL EROSION CONTROL
8	EC03	INTERIM EROSION CONTROL
9	EC04	INTERIM EROSION CONTROL
10	EC05	FINAL EROSION CONTROL
11	EC06	FINAL EROSION CONTROL
12	OG01	OVERALL GRADING PLAN
13	GR01	OVERLOT GRADING PLAN
14	GR02	OVERLOT GRADING PLAN
15	GR03	CROSS SECTIONS (SHEPARD AVE SWALE)
16	RD01	ASPEN ST. – OWEN AVE. PLAN & PROFILE 1
17	RD02	ASPEN ST. – OWEN AVE. PLAN & PROFILE 2
18	RD03	ASPEN ST. – OWEN AVE. PLAN & PROFILE 3
19	RD04	ASPEN ST. – OWEN AVE. PLAN & PROFILE 4
20	RD05	SPRUCE ST. PLAN & PROFILE 1
21	RD06	SPRUCE ST. PLAN & PROFILE 2
27	RD07	SMITH AVE PLAN & PROFILE 1
28	RD08	SMITH AVE PLAN & PROFILE 2
22	RD09	MAPLE ST. PLAN & PROFILE 1
23	RD10	MAPLE ST. PLAN & PROFILE 2
24	RD11	W. NELSON AVE. PLAN & PROFILE
25	RD12	W MORGAN AVE. PLAN & PROFILE
26	RD13	OAK ST PLAN & PROFILE
29	RD14	CEDAR ST PLAN & PROFILE 1
30	RD15	CEDAR ST PLAN & PROFILE 2

DIDEN OF STREETS

31	CG01	CURB AND GUTTER PLAN
32	CR01	CURB RETURN PROFILE 1
33	CR02	CURB RETURN PROFILE 2
34	CR03	CURB RETURN PROFILE 3
35	ST01	STORM ALIGNMENT 1
36	ST02	STORM ALIGNMENT 1
37	ST03	STORM ALIGNMENT 2&9
38	ST04	STORM ALIGNMENT 3
39	ST05	STORM ALIGNMENT 3&4
40	ST06	STORM ALIGNMENT PINE TO PON
41	ST07	STORM INLET DETAILS
42	ST08	STORM INLET DETAILS
43	UT01	UTILITY PLAN & PROFILE SMITH
44	UT02	UTILITY PLAN & PROFILE SMITH-
45	UT03	UTILITY & PROFILE MAPLE AVE
46	UT04	UTILITY PLAN & PROFILE NELSON
47	UT05	UTILITY PLAN & PROFILE NELSON
48	UT06	UTILITY PLAN & PROFILE CEDAR
49	UT07	UTILITY PLAN & PROFILE CEDAR
50	UT08	UTILITY PLAN & PROFILE SPRUCE
51	UT09	UTILITY PLAN & PROFILE SPRUCE
52	UT10	UTILITY PLAN & PROFILE ASPEN
53	UT11	UTILITY PLAN & PROFILE ASPEN
54	UT12	UTILITY PLAN & PROFILE ASPEN
55	UT13	UTILITY PLAN & PROFILE ASPEN
56	PD01	DETENTION POND PLAN
57	PD02	DETENTION POND DETAILS
58	DT01	DETAIL 1
59	DT02	DETAIL 2
60	DT03	DETAIL 3
61	CD01	DETAIL 1
62	CD02	DETAIL 2
63	CD03	DETAIL 3
64	CD04	DETAIL 4

15' TRACT – W. NELSON AVE. 20' TRACT - W. MORGAN AVE.

VARIES (2% MIN.)

PROPERTY DESCRIPTION:

A PARCEL OF LAND LOCATED IN THE SOUTHWEST QUARTER OF SECTION 26, TOWNSHIP 2 NORTH, RANGE 64 WEST OF THE 6TH PRINCIPAL MERIDIAN, COUNTY OF WELD, STATE OF COLORADO, BEING MORE PARTICULARLY DESCRIBED AS FOLLOWS:

CONSIDERING THE SOUTH LINE OF SAID SECTION 26 TO BEAR SOUTH 89°24'19" WEST, A DISTANCE OF 2632.40 FEET BETWEEN A FOUND 3-1/4" ALUMINUM CAP MARKED "ALPHA ENGINEERING, 1/4, S26, S35, R64W, 1994, LS 25937" AT THE SOUTH QUARTER CORNER OF SAID SECTION 26 AND A FOUND 3-1/4" ALUMINUM CAP MARKED "T2N, R64W, S27, S26, S34, S35, 1999, PLS 13155" AT THE SOUTHWEST CORNER OF SAID SECTION 26 AS SHOWN HEREON, WITH ALL BEARINGS CONTAINED HEREIN RELATIVE THERETO.

BEGINNING AT THE SOUTHWEST CORNER OF SAID SECTION 26; THENCE ALONG THE WEST LINE OF THE SOUTHWEST QUARTER OF SAID SECTION 26 NORTH 00°23'34" WEST, A DISTANCE OF 1022.57 FEET TO A POINT ON THE SOUTH RIGHT-OF-WAY LINE OF THE BURLINGTON NORTHERN SANTA FE RAILROAD; THENCE ALONG SAID SOUTH RIGHT-OF-WAY LINE, NORTH 47°07'15" EAST, A DISTANCE OF 462.49 FEET TO A POINT ON THE SOUTH LINE EXTENDED OF STEWART SUBDIVISION, RECORDED IN THE RECORDS OF WELD COUNTY ON JULY 7, 1999 AT RECEPTION NO. 2704562; THENCE ALONG SAID SOUTH LINE EXTENDED AND SOUTH LINE OF STEWART SUBDIVISION NORTH 89"24'00" EAST, A DISTANCE OF 721.21 FEET TO A POINT ON THE WEST RIGHT-OF-WAY LINE EXTENDED OF CEDAR STREET, AS DESCRIBED IN RIGHT-OF-WAY DEED RECORDED IN THE RECORDS OF WELD COUNTY ON MARCH 28, 1960 IN BOOK 1554, PAGE 356; THENCE ALONG SAID RIGHT-OF-WAY LINE EXTENDED, SOUTH 01°03'59" EAST, A DISTANCE OF 47.81 FEET TO THE NORTHWEST CORNER OF SAID CEDAR STREET RIGHT-OF-WAY; THENCE ALONG THE WEST RIGHT-OF-WAY LINE OF CEDAR STREET, SOUTH 01°03'59" EAST, A DISTANCE OF 1286.02 FEET TO A POINT ON THE SOUTH LINE OF THE SOUTHWEST QUARTER OF SAID SECTION 26; THENCE ALONG SAID SOUTH LINE, SOUTH 89°24'19" WEST, A DISTANCE OF 1077.95 FEET, MORE OR LESS, TO THE SOUTHWEST CORNER OF SAID SECTION 26 AND THE POINT OF BEGINNING.

CONTAINING 31.547 ACRES MORE OR LESS.


BASIS OF BEARINGS

ASSUMING THE SOUTH LINE OF THE SOUTHWEST QUARTER OF SECTION 26, TOWNSHIP 2 NORTH, RANGE 64 WEST OF THE SIXTH PRINCIPAL MERIDIAN, AS MONUMENTED BY A NO. 6 REBAR WITH 3-1/4 INCH ALUMINUM CAP MARKED "PLS 13155" AT THE SOUTHWEST CORNER OF SAID SECTION 26 AND A NO. 6 REBAR WITH A 3-1/2 INCH ALUMINUM CAP STAMPED PLS 25937 AT THE SOUTH QUARTER CORNER OF SAID SECTION 26 TO BEAR SOUTH 89°24'23" WEST, BEING A GRID BEARING OF THE COLORADO STATE PLANE COORDINATE SYSTEM, NORTH ZONE, NORTH AMERICAN DATUM 1983/2007, A DISTANCE OF 2632.46 FEET WITH ALL BEARINGS CONTAINED HEREIN RELATIVE THERETO.


CONSTRUCTION DOCUMENTS **VISTA WEST SUBDIVISION**

LOCATED IN THE SOUTHWEST 1/4 OF SECTION 26, TOWNSHIP 2 NORTH, RANGE 64 WEST OF THE 6th PRINCIPAL MERIDIAN

TOWN OF KEENESBURG, WELD COUNTY, COLORADO



VICINITY MAP SCALE: 1'' = 2000'



WEST ROW EXISTING 60' ROW 36'F_ - F_ 12' EXISTING Q−F WIDTH VARIES (SEE PLANS) 18'┣–₢ EXISTING 5.5' WALK 6.5' EXISTING ASPHALT WIDTH VARIES 5'WALK - 16' FULL DEPTH ASPHALT TAPER MILL ON EAST SIDE WITH 2" OVERLAY PROPOSED 2.0% PROFILE GRADE VARIES VARIES 2.0% VARIE<u>S</u> PROPOSED FULL EXISTING VERTICAL CURB - EXISTING GRADE DEPTH ASPHALT & GUTTER (TYP.) **4.0** TYPICAL SECTION - CEDAR STREET PROPOSED MOUNTABLE CURB & GUTTER (TYP.)

CONTACTS:

MUNICIPALITY TOWN OF KEENESBURG 91 W. BROADWAY AVENUE KEENESBURG, CO 80643 TELEPHONE: (303) 732-4281

OWNER/APPLICANT: MSP INVESTMENT CO, LLP SUITE 940 NORTH TOWER 720 S. COLORADO BLVD. DENVER, CO 80246 TELEPHONE: (303)399-9804 EMAIL: MARCUSOMSPCOMPANIES.COM CONTACT: MARCUS PALKOWITSH

PLANNING & CIVIL ENGINEER BASELINE ENGINEERING 112 N. RUBEY DRIVE, #210 GOLDEN, CO 80403 TELEPHONE: (303) 940-9966 CONTACTS: PLANNING - LAUREN RICHARDSON

ENGINEERING - MICHAEL LUJAN

FIRE DISTRICT SOUTHEAST WELD FIRE PROTECTION DISTRICT 95 W BROADWAY STREET KEENSBURG, CO 80643 TELEPHONE: (303) 732-4203 CONTACTS: THOMAS BEACH

WATER & SANITATION DISTRICT TOWN OF KEENSBURG 91 W BROADWAY AVENUE KEENSBURG, CO 80643 TELEPHONE: (303) 732-4281

LANDSCAPING CONSILIUM DESIGN 2755 SOUTH LOCUST ST, SUITE 236 DENVER, CO 80222 CONTACT: JULIE HEDERICKSON









			Fnaineerina · Plannina · Survevina		Image: Amage:	112 N RUBEY DRIVE SUITE 210 • GOLDEN. COLORADO 80403	P. 303.940.9966 • F. 303.940.9959 • www.baselinecorp.com
DESIGNED BY	SPC	DRAWN BY	JRJ		CHECKED BY		MLL
DATE	09/22/2021	11/05/2021	12/15/2021				
PREPARED BY	MLL	MLL	MLL				
REVISION DESCRIPTION	TOWN COMMENTS	WELD COUNTY TOWN COMMENTS	SITE REVISIONS				
		TOWN OF KEENESBURG	VISTA WEST SUBDIVISION				
	L SUE	IZE		06 24	/30 "X)/20 36)21 "
SURV Job I Draw	ING N -Cove	RM Ame	otes, OF	10, CO &	/02 349		20





Know what's **below**. **Call** before you dig.

TOWN OF KEENESBURG GENERAL NOTES:

- 1. ALL WORK WITHIN THE PUBLIC ROW OR EASEMENT SHALL CONFORM TO THE TOWN OF KEENESBURG CONSTRUCTION DESIGN SPECIFICATIONS.
- 2. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS PRIOR TO COMMENCEMENT OF ANY WORK ON THE PROJECT. A PERMIT FROM PUBLIC WORKS IS REQUIRED FOR ALL CONSTRUCTION IN PUBLIC ROW OR EASEMENTS. A PRECONSTRUCTION CONFERENCE SHALL BE HELD WITH TOWN REPRESENTATIVES BEFORE A PERMIT WILL BE ISSUED.
- 3. THE CONTRACTOR SHALL NOTIFY THE TOWN PROJECT REPRESENTATIVE AT LEAST 24 HOURS PRIOR TO DESIRED INSPECTION.
- 4. IT IS THE CONTRACTOR'S RESPONSIBILITY TO NOTIFY THE OWNER/DEVELOPER, AND THE TOWN, OF ANY PROBLEMS IN CONFORMING TO THE ACCEPTED PLANS FOR ANY ELEMENT OF THE PROPOSED IMPROVEMENTS, PRIOR TO ITS CONSTRUCTION.
- 5. IT IS THE RESPONSIBILITY OF THE DEVELOPER DURING CONSTRUCTION ACTIVITIES TO RESOLVE CONSTRUCTION PROBLEMS DUE TO CHANGED CONDITIONS, OR DESIGN ERRORS ENCOUNTERED BY THE CONTRACTOR DURING THE PROGRESS OF ANY PORTION OF THE PROJECT. IF, IN THE OPINION OF THE TOWN, THE MODIFICATIONS PROPOSED BY THE DEVELOPER, TO THE ACCEPTED PLANS, INVOLVE SIGNIFICANT CHANGES TO THE CHARACTER OF THE WORK, OR TO THE FUTURE CONTIGUOUS PUBLIC OR PRIVATE IMPROVEMENTS, THE DEVELOPER SHALL BE RESPONSIBLE FOR RESUBMITTING THE REVISED PLANS TO THE TOWN OF KEENESBURG FOR ACCEPTANCE PRIOR TO ANY FURTHER CONSTRUCTION RELATED TO THAT PORTION OF THE PROJECT. ANY IMPROVEMENTS NOT CONSTRUCTED IN ACCORDANCE WITH THE ACCEPTED PLANS, OR THE ACCEPTED REVISED PLANS, SHALL BE REMOVED AND RECONSTRUCTED ACCORDING TO THE APPROVED PLAN.
- 6. THE CONTRACTOR SHALL BE SOLELY AND COMPLETELY RESPONSIBLE FOR THE CONDITIONS AT AND ADJACENT TO THE JOB SITE, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY, DURING THE PERFORMANCE OF THE WORK. THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND SHALL NOT BE LIMITED TO NORMAL WORKING HOURS. THE DUTY OF THE TOWN TO CONDUCT CONSTRUCTION REVIEW OF THE CONTRACTOR'S PERFORMANCE IS NOT INTENDED TO INCLUDE REVIEW OF THE ADEQUACY OF THE CONTRACTOR'S SAFETY MEASURES IN, ON, OR NEAR THE CONSTRUCTION SITE.
- 7. THE CONTRACTOR SHALL PROVIDE ALL LIGHTS, SIGNS, BARRICADES, FLAG PERSONS, OR OTHER DEVICES NECESSARY TO PROVIDE FOR PUBLIC SAFETY IN ACCORDANCE WITH THE CURRENT MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION OF ALL SURVEY MONUMENTS. ANY MONUMENT THAT MUST BE DESTROYED FOR CONSTRUCTION SHALL BE REPLACED BY A REGISTERED LAND SURVEYOR. THE CONTRACTOR SHALL ENGAGE THE SERVICES OF A LICENSED SURVEYOR PRIOR TO DISTURBING ANY MONUMENTS.
- 9. PRIOR TO FINAL PLACEMENT OF SURFACE PAVEMENT, ALL UNDERGROUND UTILITY MAINS SHALL BE INSTALLED, TESTED AND ACCEPTED, AND SERVICE CONNECTIONS STUBBED OUT BEYOND THE PROPERTY LINE, WHEN ALLOWED BY THE UTILITY. SERVICE FROM PUBLIC UTILITIES AND FROM SANITARY SEWERS SHALL BE MADE AVAILABLE FOR EACH LOT IN SUCH A MANNER THAT WILL NOT BE NECESSARY TO DISTURB THE STREET PAVEMENT, CURB, GUTTER, AND SIDEWALK WHEN CONNECTIONS ARE MADE.
- 10. COPIES OF RECORD DRAWING PLANS SHALL BE SUBMITTED TO THE TOWN OF KEENESBURG PRIOR TO INITIAL ACCEPTANCE OF THE PUBLIC IMPROVEMENTS.
- 11. BASIS OF BEARINGS: ASSUMING THE SOUTH LINE OF THE SOUTHWEST QUARTER OF SECTION 26, TOWNSHIP 2 NORTH, RANGE 64 WEST OF THE SIXTH PRINCIPAL MERIDIAN, AS MONUMENTED BY A NO. 6 REBAR WITH 3-1/4 INCH ALUMINUM CAP MARKED "PLS 13155" AT THE SOUTHWEST CORNER OF SAID SECTION 26 AND A NO. 6 REBAR WITH A 3-1/2 INCH ALUMINUM CAP STAMPED PLS 25937 AT THE SOUTH QUARTER CORNER OF SAID SECTION 26 TO BEAR SOUTH 89°24'23" WEST, BEING A GRID BEARING OF THE COLORADO STATE PLANE COORDINATE SYSTEM, NORTH ZONE, NORTH AMERICAN DATUM 1983/2007, A DISTANCE OF 2632.46 FEET WITH ALL BEARINGS CONTAINED HEREIN RELATIVE THERETO.
- 12. BENCHMARK: A SET NO. 5 REBAR WITH A 2-1/2 INCH ALUMINUM CAP "CP WIND", ELEVATION = 4936.01'
- 13. FOR SURVEY CONTROL AND DATUM INFORMATION, CONTACT BASELINE CORPORATION.
- 14. COORDINATES SHOWN ON THIS DRAWING ARE MODIFIED COLORADO STATE PLANE NORTH ZONE. TO REDUCE TO STATE PLANE COORDINATES, SCALE AT 0.99972715 (1.0002729245) ABOUT THE ORIGIN (0,0).
- 15. ALIQUOT MONUMENTS DESTROYED DURING CONSTRUCTION TO BE REPLACED BY PROFESSIONAL LAND SURVEYOR.

STANDARD EROSION AND SEDIMENT CONTROL NOTES:

- 1. LANDOWNERS AND/OR CONTRACTORS ARE RESPONSIBLE FOR OBTAINING A PERMIT FOR STORMWATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES FROM THE COLORADO DEPARTMENT OF HEALTH & ENVIRONMENT (CDPHE), AT LEAST TEN (10) DAYS PRIOR TO THE START OF CONSTRUCTION ACTIVITIES IF CONSTRUCTION ACTIVITIES WILL DISTURB 1 (ONE) OR MORE ACRES OF LAND, OR IF THE PROJECT BELONGS TO A COMMON PLAN OF DEVELOPMENT THAT WILL DISTURB 1 (ONE) OR MORE ACRES. IN THE EVENT THAT LOT/PARCEL, WHICH BELONGS TO A COMMON PLAN OF DEVELOPMENT THAT DISTURBED 1 (ONE) OR MORE ACRES, IS SOLD THEN THE NEW LANDOWNER AND/OR CONTRACTOR IS RESPONSIBLE FOR OBTAINING PERMIT COVERAGE FOR THAT LOT/PARCEL.
- 2. LANDOWNERS AND/OR CONTRACTORS ARE RESPONSIBLE FOR OBTAINING A GRADING PERMIT FROM THE TOWN IF CONSTRUCTION ACTIVITIES WILL DISTURB 1 (ONE) OR MORE ACRES OF LAND, OR IF THE PROJECT BELONGS TO A COMMON PLAN OF DEVELOPMENT THAT WILL DISTURB 1 (ONE) OR MORE ACRES.
- 3. THE PERMITTED LANDOWNER AND/OR CONTRACTOR MUST KEEP A COPY OF THE CDPHE STORMWATER DISCHARGE PERMIT, STORMWATER MANAGEMENT PLAN (SWMP) AND INSPECTION LOG AVAILABLE ON-SITE THROUGHOUT THE DURATION OF THE PROJECT, AND FOR AN ADDITIONAL THREE (3) YEARS AFTER INACTIVATION FORM IS FILED WITH THE STATE.
- 4. THE PERMITTED LANDOWNER AND/OR CONTRACTOR MAY INACTIVATE THE STATE PERMIT WHEN FINAL STABILIZATION IS REACHED. AS LONG AS ALL SOIL DISTURBING ACTIVITIES AT THE SITE HAVE BEEN COMPLETED AND A UNIFORM VEGETATIVE COVER HAS BEEN ESTABLISHED WITH A DENSITY OF AT LEAST 70 PERCENT OF PRE-DISTURBANCE LEVELS, OR EQUIVALENT PERMANENT, PHYSICAL EROSION REDUCTION METHODS HAVE BEEN EMPLOYED.
- 5. THE PERMITTED LANDOWNER AND/OR CONTRACTOR MUST PERFORM INSPECTIONS OF ALL BMPS EVERY 14 DAYS AND ALSO AFTER ANY SIGNIFICANT STORM EVENT (RAIN OR SNOWMELT) THAT MAY CAUSE EROSION TO ENSURE THAT BMPS ARE FUNCTIONING PROPERLY. INSPECTION LOGS MUST BE KEPT WITH THE SWMP. ALL NECESSARY MAINTENANCE AND REPAIR SHALL BE COMPLETED IMMEDIATELY.
- 6. ALL CONSTRUCTION PROJECTS, WHETHER THEY DISTURB LESS OR MORE THAN 1 (ONE) ACRE SHALL INSTALL, MAINTAIN AND REPAIR EROSION AND SEDIMENT CONTROL BEST MANAGEMENT PRACTICES (BMPS) ACCORDING TO THE STORMWATER MANAGEMENT PLAN (SWMP) AND/OR EROSION CONTROL PLAN TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION. EROSION & SEDIMENT CONTROL MEASURES (BMPS) MUST BE INSTALLED PRIOR TO GRADING OR LAND DISTURBING ACTIVITIES.
- 7. LANDOWNERS AND/OR CONTRACTORS MUST ENSURE THAT VEHICLES DO NOT TRACK EARTH MATERIALS ONTO STREETS AND MUST IMMEDIATELY REMOVE SUCH MATERIALS IF THIS OCCURS. EITHER SWEEPING BY HAND OR THE USE OF STREET SWEEPERS IS ACCEPTABLE. FLUSHING OFF PAVED SURFACES WITH WATER IS PROHIBITED.
- 8. ALL LOADS OF CUT AND FILL MATERIAL IMPORTED TO OR EXPORTED FROM THE SITE SHALL BE PROPERLY COVERED TO PREVENT LOSS OF THE MATERIAL DURING TRANSPORTATION ON PUBLIC ROW.
- 9. THE USE OF DIRT RAMPS IS PROHIBITED. A ROCK PAD ENTRANCE SHOULD BE INSTALLED WHERE CONSTRUCTION VEHICLES NEED TO ENTER OR EXIT FROM AN UNPAVED AREA INTO A PAVED ROAD.
- 10. LANDOWNERS AND/OR CONTRACTORS ARE RESPONSIBLE FOR CONTROLLING WASTE SUCH AS DISCARDING BUILDING MATERIALS, CONCRETE TRUCK WASHOUT, CHEMICALS, LITTER AND SANITARY WASTE, AS APPLICABLE.
- 11. WASTE COLLECTION AREAS SHOULD BE LOCATED AWAY FROM THE STORM DRAINAGE SYSTEM. CONSIDERATION SHOULD BE GIVEN TO COVERING WASTE STORAGE DUMPSTERS, TO BE ABLE TO CONTAIN WINDBLOWN MATERIALS.
- 12. THE DISCHARGE OF ANY WATER CONTAMINATED BY WASTE PRODUCTS FROM CUTTING OPERATIONS TO THE STORM SEWER SYSTEM IS PROHIBITED. ALL STORM SEWER FACILITIES ADJACENT TO ANY LOCATION WHERE PAVEMENT CUTTING OPERATIONS INVOLVING ROAD/CONCRETE CUTTING NEED TO BE PROTECTED. ALL WASTE PRODUCTS GENERATED DURING CUTTING ACTIVITIES MUST BE REMOVED ON A DAILY BASIS.
- 13. WATER USE TO CLEAN CEMENT/CONCRETE TRUCKS SHALL BE DISCHARGED INTO A CONCRETE WASHOUT AREA (CWA). THE PREDEFINED CONTAINMENT AREA MUST BE IDENTIFIED WITH A SIGN, AND SHALL ALLOW THE LIQUIDS TO INFILTRATE, EVAPORATE OR DRY OUT. DRIED CONCRETE WASTE SHALL BE REMOVED AND PROPERLY DISPOSED OF.
- 14. THE DISCHARGE OF SANITARY WASTE IN THE STORM SEWER SYSTEM IS PROHIBITED. PORTABLE TOILETS MUST BE PLACED ON PERMEABLE SURFACES, AWAY FROM THE CURBSIDE AND AWAY FROM STORM INLETS AND/OR DRAINAGE WAYS.
- 15. SPILL PREVENTION AND CONTAINMENT BMP'S FOR CONSTRUCTION MATERIALS, WASTE AND FUEL MUST BE PROVIDED. SPILLS THAT MAY REACH THE STORM SEWER SYSTEM MUST BE REPORTED ACCORDING TO FEDERAL, STATE AND COUNTY REGULATIONS.
- 16. STORM INLETS WITHIN AND/OR ADJACENT TO THE CONSTRUCTION SITE SHOULD BE PROTECTED. ANY PONDING OF STORMWATER AROUND INLET PROTECTION MUST NOT CAUSE EXCESSIVE INCONVENIENCE OR DAMAGE TO ADJACENT AREAS OR STRUCTURES.
- 17. RUNOFF FROM STOCKPILED AREA MUST BE CONTROLLED. SOILS THAT WILL BE STOCKPILED FOR MORE THAN 30 DAYS SHALL BE PROTECTED FROM WIND AND WATER EROSION WITHIN 14 DAYS OF STOCKPILE CONSTRUCTION (MULCH & SEEDING, EROSION CONTROL BLANKETS, ETC). ANY STOCKPILE LOCATED NEAR A DRAINAGE WAY, MUST BE PROVIDED WITH ADDITIONAL BMPS PROTECTION SUCH AS TEMPORARY DIKES OR SILT FENCE.

STANDARD EROSION AND SEDIMENT CONTROL NOTES (CONTINUED:

- 18. NATURAL VEGETATION SHALL BE PRESERVED AND PROTECTED WHENEVER POSSIBLE. REMOVAL OR DISTURBANCE OF EXISTING VEGETATION SHALL BE LIMITED TO THE AREA REQUIRED FOR IMMEDIATE CONSTRUCTION OPERATIONS. DISTURBED AREAS THAT MAY NOT BE AT FINAL GRADE BUT WILL REMAIN DORMANT (UNDISTURBED) FOR LONGER THAN 30 DAYS SHOULD BE STABILIZED WITHIN 14 DAYS.
- 19. FUGITIVE DUST EMISSIONS RESULTING FROM GRADING ACTIVITIES AND/OR WIND SHALL BE CONTROLLED.
- 20. ALL TEMPORARY EROSION AND SEDIMENT CONTROL MEASURES SHALL BE REMOVED AFTER THE SITE HAS ACHIEVED FINAL STABILIZATION AND THE PERMIT HAS BEEN INACTIVATED. THE STORMWATER VOLUME CAPACITY OF PONDS MUST BE RESTORED, AND STORM SEWER LINES AND/OR DRAINAGE INFRASTRUCTURE SHOULD BE CLEANED UPON COMPLETION OF PROJECT.
- 21. CONDITIONS IN THE FIELD MAY WARRANT EROSION AND SEDIMENT CONTROL MEASURES IN ADDITION TO WHAT IS SHOWN ON THE SWMP AND/OR EROSION CONTROL PLAN. THE LANDOWNER OR CONTRACTOR SHALL IMPLEMENT WHATEVER MEASURES ARE DETERMINED NECESSARY, AS DIRECTED BY THE COUNTY.
- 22. ALL AREAS NOT LANDSCAPED OR COVERED BY OTHER PERMANENT SURFACES SHALL BE RESEEDED PER TABLE RV-10 GRASS SEEDING TABLES BASED ON RANGE SITES FOR SANDY MEADOW AND SANDY PLAINS SITE CONDITIONS, AS CONTAINED IN WELD COUNTY CODE, CHAPTER 8, ARTICLE XI STORM DRAINAGE CRITERIA, DIVISION I GENERAL PROVISIONS, CHAPTER 12 REVEGETATION.


LEGEND

EXISTING LINET	YPES
81	
— — — 5280—	
xxx	x
>	<u>></u>
W	
WS	- WS
SAN	- SAN
SS	- SS ———
ST	- ST
OHU	- OHU
т	- T

<u>PROPOSED LINETYPES</u>
¥
W WS SAN SS
ОНU Т

MINOR CONTOUR (1' INTERVAL)
MAJOR CONTOUR (5' INTERVAL)
PROPERTY BOUNDARY
LOT LINE
EASEMENT
EDGE OF ASPHALT
EDGE OF GRAVEL
CURB AND GUTTER (SPILL/CATCH)
WRE FENCE
WIRE FENCE DITCH FLOWLINE
DITCH FLOWLINE
DITCH FLOWLINE WATER LINE
DITCH FLOWLINE WATER LINE WATER SERVICE
DITCH FLOWLINE WATER LINE WATER SERVICE SANITARY SEWER MAIN
DITCH FLOWLINE WATER LINE WATER SERVICE SANITARY SEWER MAIN SANITARY SEWER SERVICE
DITCH FLOWLINE WATER LINE WATER SERVICE SANITARY SEWER MAIN SANITARY SEWER SERVICE STORM SEWER

EXISTING <u>SYMBOLS</u>	Proposed <u>Symbols</u>	
25.4±	25.36	SPOT ELEVATION
3:1	► <u>3:1</u>	NOMINAL SLOPE ON CUT OR FILL
	\rightarrow	FLOW DIRECTION, TYPICALLY ON PAVED SURFACES
		FLOW DIRECTION, TYPICALLY IN GRASSED SWALE
	Ô	FIRE HYDRANT
$\overset{\mathbb{W}}{\boxtimes}$	M	WATER VALVE
S	S	SANITARY MANHOLE
	\square	CONCRETE FLARED END SECTION
-;4;-	*	LIGHT POLE
Ø	Ø	POWER POLE
<u> </u>	.	SIGN
MB		MAILBOX



LEGEND

	PROPERTY BOUNDARY
	SECTION LINE
	MINOR CONTOUR (2' INTERVAL)
— — — 5280— — —	MAJOR CONTOUR (10' INTERVAL)
	RIGHT-OF-WAY
	LOT LINE
	EASEMENT
	EDGE OF ASPHALT
	EDGE OF GRAVEL
	CURB AND GUTTER
ooo	CHAINLINK FENCE
W W	WATER LINE
SAN SAN	SANITARY SEWER
SAMBUL & I EGEND	


SYMBOLS LEGEND


 (\mathbb{S})

SANITARY MANHOLE

NOTES:

1. IT IS THE OWNER AND/OR THE CONTRACTORS RESPONSIBILITY TO ATTAIN ALL APPROPRIATE PERMITS AND REVIEW APPROVALS FROM THE TOWN OF KEENSBURG RESPECTIVELY.










- SPECIFICATIONS AND ILLUSTRATIONS ARE LOCATED IN THE COLORADO DIVISION OF HIGHWAYS M AND S STANDARDS.
- BY THE TOWN OF KEENESBURG. ALL DISCREPANCIES IDENTIFIED DURING THE FIELD INSPECTION MUST BE CORRECTED BEFORE THE TWO-YEAR WARRANTY PERIOD WILL BEGIN.
- UNDERGROUND UTILITIES.
- THE SIDEWALK FOR ALL SIGNS IN AREAS OF PEDESTRIAN TRAFFIC.


- TRAFFIC CODE.









- 5. GUIDELINES WITH THE LOCAL AGENCY PERMIT AND STANDARDS AND SPECIFICATIONS SHALL BE FOLLOWED AND MAINTAINED.
- 6. AN APPROVED COPY OF THE EROSION AND SEDIMENT CONTROL PLAN AND STORMWATER MANAGEMENT PLAN SHALL BE KEPT ON SITE AT ALL TIMES.
- 7. LOCATION OF BMPS MAY VARY BASED ON THESE PLANS DUE TO PROGRESS AND PHASING OF CONSTRUCTION ACTIVITIES.
- 8. SITE BMPS SHALL BE MAINTAINED AND REPAIRED IF DAMAGED IMMEDIATELY, SITE INSPECTIONS SHALL
- OCCUR EVERY 7-DAYS, AND WITHIN 24-HOURS OF ANY PRECIPITATION EVENT. 9. REFER TO STORMWATER MANAGEMENT PLAN (SWMP) FOR EROSION AND SEDIMENT CONTROL REQUIREMENTS.
- 10. INSTALL CHECK DAMS EVERY 200 FT IN DIVERSION DITCH.




EC01








ACCORDANCE WITH MILE HIGH FLOOD DISTRICT CRITERIA.




EC03









EC06







OVERLOT GRADING PLAN I

- 6. MAX SLOPE = 3:1
- 7. THESE PLANS DO NOT REFLECT STREET CORES. 8. TOP OF FOUNDATION IS MINIMUM ELEVATION. REFER TO PLOT
- PLAN (BY OTHERS) FOR FINAL DESIGN.
- 9. SEE SHEETS EC01-EC06 FOR EROSION CONTROL PLANS. 10. DRIVEWAYS ARE TYPICALLY LOCATED ON THE HIGH SIDE OF THE LOT. DRIVEWAYS ON CONNER LOTS ARE LOCATED ON THE SIDE AWAY FROM THE INTERSECTION.
- 11. SANITARY SEWER SERVICE LINES ARE TYPICALLY LOCATED ON THE LOW SIDE OF THE LOT, REFER TO OVERALL UTILITY PLAN FOR LOCATIONS.

AREA OF DISTURBANCE = 32.38 ACRES

OVERLOT	GRADING	EARTHWORK	SUMMARY	
SURFACE	CUT	=	+88,537 CU-YD	
SURFACE	FILL	=	-76570 CU-YD	
NET		=	+11,968 CU-YD	(CUT)

1. THE ABOVE EARTHWORK CALCULATIONS ARE AN ENGINEER'S ESTIMATE AND NOT TO BE USED FOR CONTRACTUAL OR BIDDING PURPOSES. CONTRACTOR IS RESPONSIBLE FOR PROVIDING THEIR OWN EARTHWORK ESTIMATE.


EARTHWORK SUMMARY DOES NOT INCLUDE SHRINKAGE OF FILL MATERIAL. 3. PAVEMENT AND HARDSCAPE AREAS ARE ACCOUNTED FOR IN THIS ESTIMATE.




Know what's **below. Call** before you dig.

SURV JOB			REVISION DESCRIPTION	PREPARED BY DATE	DESIGNED BY	
ing n GRA	BASI		TOWN COMMENTS	MLL 09/22/2021	SPC	
		EDMN OF KEENESBURG	WELD COUNTY TOWN COMMENTS	MLL 11/05/2021	DRAWN BY	
.dwg OF	COR	gg VISTA WFST SUBDIVISION	SITE REVISIONS	MLL 12/15/2021	JRJ	Fnainearina - Plannina - Survevina
10/	06, 24"					
7 /02/ 3490 4	Апо /30, / X				CHECKED BY	
/202	n /20: 36"	BI OVFRALL GRADING PLAN				112 N RUBEY DRIVE, SUITE 210 • GOLDEN, COLORADO 80403
						P: 303.940.9966 • F: 303.940.9959 • www.baselinecorp.com


OG01




GR01





N: \co3490 - Summerfield - Keenesburg\Drawings\Construction Plans\Grading\3490-GRADING.dwg, 12/15/2021 5:37:20 PM, Jake Jack





sheet 14 of 64 GR02





























































RD04






















4948.87		ERLINE	4949.94 4951.8	/ @ CEN1	4922.6 Function Agen ag		4950.73 4953.7	4950.88	4954.0 4950.96	4954.4 4050.05	4954.6	4950.86 4954.9	4950.68	4955.3 4950.44	4950.19	4955.9	4949.94 4956.2
	STA.=3 ELEV.=	ST – W. NE 9+32.94 4948.46		-													
	CEN	POSED GRAL ITERLINE (TY	P.)														
					1.00%										-1.0	00%	
	BVCS: 39+69.59	K: 3:	50.00	EVCS: 40+19.59 V EVCE: 4950.19		BVCS: 40+59.92 BVCE: 4950.59								EVCS: 42+09.92 V EVCE: 4950.59			BVCS: 42+85.94 BVCS: 42+85.94 BVCE: 4949.83 BVCE: 4949.83
		HIGH PT STA HIGH PT ELE PVI STA: PVI ELEV: K: 3	V: 49 39+94 4949	950.19 4.59 1.94					HIGH PVI PVI	PT STA: 41+ PT ELEV: 499 STA: 41+34 ELEV: 4951. K: 75.00 LVC: 150.00	50.97 .92						PVI STA: PVI ELEV: K: 4



























RD13







79-	+00			80	+00			81	+00			82	+00		82+56	
4952.69		4952.86	4953.04 4953.4	4953.6 4953.6 4053.30		4953.9 4953.74	4954.0 4953.91			4954.5 4954.44	4954.7 4954.61					
elevati Erline	on @ (TYP.) ¯	EXIS CEN	iting elevatio Terline (typ.)N @												
												W. OW	En ave. inte Sta.=8 Elev.=	RSECTION 32+56.27 =4954.43	4950)
			PIPE			0.	70%			=						F
	EVCS: 79+13.63 EVCE: 4952.78			ED GRADE @								BVCS: 8	ELEV:)
	8											81+89.21 : 4954.71	82+10.21 4954.78		EVCS: 82+55.21 EVCE: 4954.45 096	
5													PVI STA: 8 PVI ELEV: K: 30 A: -2. LVC: 6	20% 6.00		
														4954.94 <u></u>)







4 CD01 CD01







Know what's below. Call before you dig.













-0+25







_ _ _














4








 $\langle 7 \rangle$





CR01


























(15)

























(17)






















																1						
EX PIF	STING GRADE PE CENTERLINE	©					STM MH P7	·\Z ≥ 4 _ ,	= (N) N L (L) =	INV. 0UI (E) = 4945.12												SEE SHEET 2103
		100-YR ST	DRM HGL	<u> </u>			<u> </u>															MA ICHLINE S
												· · · · · · · · · · · · · · · · · · ·			AUL IN							495
	SANITARY (12" STA = TOP =	CROSSING DIA. PVC _ 13+20.00 4944.68		1 .5'									57.0 LF. 24		@ 0.9%							
						2				~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~							N _			~		493
4953.42	4959.2 4952.87		3+00	4951.93	4956.4	4951.53 4955.1	4951.18	4953.5 4050 88	4950.00	4950.62	4950.2	4950.37	4948.6 4050 13	4947.0	4949.87	4945.4	4949.02 4943.9	4949.37	4942.5	4949.12	C.1494	4948.87 4940.8


















004 ER TEE .37 SS MH 14	STA. 32+90 CONST. 4' DIA OUTSIDE DROP MH RIM = 4951.7 INV. IN (N) = 4943.55 INV. IN (W) = 4930.21	DEPTH = 21.8'				4
	T. 5 LF 8" PVC 45 DEG. STA = 33+	1.5'	45 DEG. BEND STA = 33+35.07 5 DEG. BEND STA = 33+55.04 CONS STORM CROSSING 18" DIA. RCP STA = 33+45.12 BOTTOM = 4945.69 ST. 5 LF 8" PVC PIPE EG. BEND = 33+50.07	T. 173 LF 8" PVC PIPE -	STA. 35+27.60 STA. 35+27.60 STA. 35+27.60 NV:=4943.29 INV:=4943.20	SS MH 29 STA. 35+30.07 CONST. 4' DIA MH RIM = 4949.0 INV. IN (W) = 4928.81 INV. OUT (E) = 4928.61 DEPTH = 20.4' 4!
			10 LF 8" PVC PIPE CONST. 241 LF. 12" SANITARY SEWER LINE			
FG: 4952.77 EG: 4958.4 FG: 4952.29 EG: 4957.4 EG: 4957.4	FG: 4951.85 EG: 4956.1	EG: 4951.46 EG: 4954.7 EG: 4951.12 EG: 4953.2 EG: 4953.2	EG: 4951.5 EG: 4950.58 EG: 4949.9 FG: 4950.33	EG: 4948.3 FG: 4950.08 EG: 4946.7 EG: 4949.83 FG: 4949.83 EG: 4945.1	FC: 4949.58 EG: 4943.6 FC: 4949.33 EG: 4942.2 EG: 4942.2 FC: 4040.08	FG: 4949.08 EG: 4941.3 FG: 4948.83 EG: 4940.7 EG: 4948.58 FG: 4948.58 FG: 4948.58











UTO2





















	TING GRADE (CENTERLINE													- 4 9
			FINISHED	GRADE @		WATER CROS	SING		STA. Cons Rim = Inv.	H 02 81+41.27 T. 4' DIA MH = 4954.3 OUT (S) = 49 H = 11.7'				-49
LF.	8" PVC		ROAD CEN		<u>َ</u> _	6" DIA. DIP STA = 80+6 BOTTOM = 4	PIPE 60.39			1 = 11.7				-
R U	NE @ 0.5%													-49
														-49
FG: 4953.04	EG: 4953.4 FG: 4953.21	EG: 4953.6 F G: 4953.39	EG: 4953.8 FG: 4953.56	EG: 4953.9 FG: 4953.74	EG: 4954.0 FG: 4953.91	EG: 4954.1 FG: 4954.09	EG: 4954.3 FG: 4954.26	EG: 4954.5 FG: 4954.44	EG: 4954.7 FG: 4954.61	EG: 4954.9 FG: 4954.77	EG: 4955.1 FG: 4954.75	EG: 4955.0 FG: 4954.52		-49
							 ⊦00				+00		82+] ⊥7۴







1: \co3490 - Summerfield - Keenesburg\Drawings\Construction Plans\Utility\3490 UTILITY P&P.dwg, 12/15/2021 5:56:39 PM, Jake Jackson








SHEET 51 **OF** 64 UT09
















	FG: 4966.36		PIPI	7777		
	ΕG: 490α.			(
	FG: 4966.54 EG: 4968.4			CONST.		
	FG: 4966 73			233 LF		
2	EG: 4968.7	ER LINE (2)	0 LF. 8" PV	8" PVC PIPI		
25+00	FG: 4966.92 EG: 4968.7	1111111				
	FG: 4967.11	<u> </u>		7/7///////		
	EG: 4968.6 FG: 4967.29					
	EG: 4968.5					SS MH 20 514 20
	EG: 4968.4					CONST. 4' DIA MH CONST. 4' DIA MH RIM = 4967.0 INV. IN (SW) = 4954.00
26+	FG: 4967.53					V. OUT (NE) = 4953.80 DEPTH = 13.0 ²
·00	EG: 4968.5 FG: 4967.47					
	EG: 4968.6 EC: 4067 77					STA. 25- 8"x6" W/ INV.=496
		22				A TE
	EG: 4968.6 FG: 4966.96	CONST. SANITARY S		CONS		ER TEE
2	EG: 4968.7	225 lf. 8" Sewer line		T. 212 LF 8		
7+	FG: 4966.51	777		3" 22		
-00	EG: 4968.7	1111111111		PVC PIPE		CC INV. IN INV. OUT
	FG: 4965.95	222				ons R
	EG: 4968.6 FG: 4965.37					SS MH 12 A. 27+95.46 T. 4' DIA MH IM = 4964.2) = 4952.68) = 4952.48 EPTH = 11.6
	EG: 4968.4					
	FG: 4964.80	22/22			+	27+95 22° B =4955
	EG: 4968.3				 \	END
28						INF SFF SHFFT 11715
8+(











CONSTRUCTION FENCE MAINTENANCE NOTES

DOCUMENTED THOROUGHLY.

DISCOVERY OF THE FAILURE.

DIFFERENCES ARE NOTED.

JURISDICTION.

EROSION, AND PERFORM NECESSARY MAINTENANCE.

SM-3 1. INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE, INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE 2. FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE 3. WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON 4. CONSTRUCTION FENCE SHALL BE REPAIRED OR REPLACED WHEN THERE ARE SIGNS OF DAMAGE SUCH AS RIPS OR SAGS. CONSTRUCTION FENCE IS TO REMAIN IN PLACE UNTIL THE UPSTREAM DISTURBED AREA IS STABILIZED AND APPROVED BY THE LOCAL JURISDICTION. 5. WHEN CONSTRUCTION FENCES ARE REMOVED, ALL DISTURBED AREAS ASSOCIATED WITH THE INSTALLATION, MAINTENANCE, AND/OR REMOVAL OF THE FENCE SHALL BE COVERED WITH TOPSOIL, SEEDED AND MULCHED, OR OTHERWISE STABILIZED AS APPROVED BY LOCAL NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN (DETAIL ADAPTED FROM TOWN OF PARKER, COLORADO, NOT AVAILABLE IN AUTOCAD) /15 CF-3 SITE \Box LLP. NO $\overline{\mathcal{O}}$ g SUBDIVIS INVESTMENT -Ś \geq \triangleleft -. С \geq MSP 님 PREPARED UNDER THE DIREC SUPERVISION OF FOR AND ON BEHALF OF BASELINE CORPORATION INITIAL SUBMITTAL 06/30/20 DRAWING SIZE 24" X 36" URVEY FIRM SURVEY DAT SURVEY FIRM 10/02/202 JOB NO. CO3490 November 2010 DRAWING NAME 3490—Cover, Notes, & Details.dv **SHEET** 58 OF 64

November 2010

Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3

EC-6 Rolled Erosion Control Products (RECP

EROSION CONTROL BLANKET INSTALLATION NOTES

1. SEE PLAN VIEW FOR: -LOCATION OF ECB.

BLANKET

-TYPE OF ECB (STRAW, STRAW-COCONUT, COCONUT, OR EXCELSIOR). -AREA, A, IN SQUARE YARDS OF EACH TYPE OF ECB.

2. 100% NATURAL AND BIODEGRADABLE MATERIALS ARE PREFERRED FOR RECPS, ALTHOUGH SOME JURISDICTIONS MAY ALLOW OTHER MATERIALS IN SOME APPLICATIONS.

3. IN AREAS WHERE ECBs ARE SHOWN ON THE PLANS, THE PERMITTEE SHALL PLACE TOPSOIL AND PERFORM FINAL GRADING, SURFACE PREPARATION, AND SEEDING AND MULCHING. SUBGRADE SHALL BE SMOOTH AND MOIST PRIOR TO ECB INSTALLATION AND THE ECB SHALL BE IN FULL CONTACT WITH SUBGRADE. NO GAPS OR VOIDS SHALL EXIST UNDER THE

4. PERIMETER ANCHOR TRENCH SHALL BE USED ALONG THE OUTSIDE PERIMETER OF ALL BLANKET AREAS.

5. JOINT ANCHOR TRENCH SHALL BE USED TO JOIN ROLLS OF ECBs TOGETHER (LONGITUDINALLY AND TRANSVERSELY) FOR ALL ECBs EXCEPT STRAW WHICH MAY USE AN OVERLAPPING JOINT

6. INTERMEDIATE ANCHOR TRENCH SHALL BE USED AT SPACING OF ONE-HALF ROLL LENGTH FOR COCONUT AND EXCELSIOR ECBs.

7. OVERLAPPING JOINT DETAIL SHALL BE USED TO JOIN ROLLS OF ECBs TOGETHER FOR ECBs ON SLOPES. 8. MATERIAL SPECIFICATIONS OF ECBs SHALL CONFORM TO TABLE ECB-1.

9. ANY AREAS OF SEEDING AND MULCHING DISTURBED IN THE PROCESS OF INSTALLING ECBS SHALL BE RESEEDED AND MULCHED.

10. DETAILS ON DESIGN PLANS FOR MAJOR DRAINAGEWAY STABILIZATION WILL GOVERN IF DIFFERENT FROM THOSE SHOWN HERE.

1	TABLE ECB-1.	ECB MATERIA	AL SPECIFICAT	IONS
TYPE	COCONUT CONTENT	STRAW CONTENT	EXCELSIOR CONTENT	RECOMMENDED NETTING**
STRAW*	_	100%	-	DOUBLE/ NATURAL
STRAW- COCONUT	30% MIN	70% MAX	-	DOUBLE/ NATURAL
COCONUT	100%	-		DOUBLE/ NATURAL
EXCELSIOR	-	<u> </u>	100%	DOUBLE/ NATURAL

*STRAW ECBS MAY ONLY BE USED OUTSIDE OF STREAMS AND DRAINAGE CHANNEL. **ALTERNATE NETTING MAY BE ACCEPTABLE IN SOME JURISDICTIONS

RECP-8


Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3

Erosion Control Products (RECP)EC-6	<u>SC-5</u>
ROSION CONTROL BLANKET MAINTENANCE NOTES. . INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS	1½" (MINUS) CRUSH
POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE ROSION, AND PERFORM NECESSARY MAINTENANCE.	ENCLOSED IN WIRE
2. FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN FFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.	
WHERE BMP'S HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE. CECB'S SHALL BE LEFT IN PLACE TO EVENTUALLY BIODEGRADE, UNLESS REQUESTED TO BE	O" ON BEDROCK OR HARD SURFACE, 2"
EMOVED BY THE LOCAL JURISDICTION. ANY ECB PULLED OUT, TORN, OR OTHERWISE DAMAGED SHALL BE REPAIRED OR REINSTALLED. ANY SUBGRADE AREAS BELOW THE GEOTEXTILE THAT HAVE ERODED TO CREATED	ROCK SOCK SECTION
VOID UNDER THE BLANKET, OR THAT REMAIN DEVOID OF GRASS SHALL BE REPAIRED, RESEEDED AND MULCHED AND THE ECB REINSTALLED.	ANY GAP AT JO
<u>OTE:</u> MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. ONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN IFFERENCES ARE NOTED.	AMOUNT OF 12 WITH ADDITIONAL ROCK SOCK,
DETAILS ADAPTED FROM DOUGLAS COUNTY, COLORADO AND TOWN OF PARKER COLORADO, NOT AVAILABLE IN AUTOCAD)	TYP
	ROCK SOCK JOINTING
	ROCK_SOCK_INSTALLATION_NOTES
	1. SEE PLAN VIEW FOR: -LOCATION(S) OF ROCK SOCKS.
	2. CRUSHED ROCK SHALL BE 1½" (MINUS) IN S AND SHALL COMPLY WITH GRADATION SHOWN ON
	3. WIRE MESH SHALL BE FABRICATED OF 10 GA MAXIMUM OPENING OF ½", RECOMMENDED MINIMU
	4. WIRE MESH SHALL BE SECURED USING "HOG ALONG ALL JOINTS AND AT 2" CENTERS ON END
	5. SOME MUNICIPALITIES MAY ALLOW THE USE O MESH FOR THE ROCK ENCLOSURE. <u>RS-1. ROCK SOCK PE</u>
010 Urban Drainage and Flood Control District RECP-9 Urban Storm Drainage Criteria Manual Volume 3	RS-2 Urban Drainage and Flood C
6	
Urban Storm Drainage Criteria Manual Volume 3	RS-2 Urban Drainage and Flood Co Urban Storm Drainage Criteria
Urban Storm Drainage Criteria Manual Volume 3 Silt Fence (SF)	RS-2 Urban Drainage and Flood Co Urban Storm Drainage Criteria
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES - SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION	RS-2 Urban Drainage and Flood Co Urban Storm Drainage Criteria
Urban Storm Drainage Criteria Manual Volume 3 Silt Fence (SF) SILT FENCE INSTALLATION NOTES . SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER	RS-2 Urban Drainage and Flood Co Urban Storm Drainage Criteria
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION_NOTES . SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION T LEAST SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW ROOM FOR ONDING AND DEPOSITION.	RS-2 Urban Drainage and Flood Co Urban Storm Drainage Criteria
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION T LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, AND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL E USED. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING.	RS-2 Urban Drainage and Flood C Urban Storm Drainage Criteria Stockpile Management (SP)
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION T LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING AND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENDING AND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENDING SAND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENDING AND DEPOSITION. A COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. SUMPACTION SHALL BE SUCH THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR ENCH BY HAND. A SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD BE INO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. SILT FENCE FABRIC SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES	RS-2 Urban Drainage and Flood C Urban Storm Drainage Criteria Stockpile Management (SP)
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION 1 LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION 1 LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW ROOM FOR ONDING AND DEPOSITION. 4. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL 6. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 1. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 1. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 1. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 1. COMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 2. SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD 3. SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD 4. SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD 4. SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD 5. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. 5. SILT FENCE FABRIC SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES 10 NALLS WITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC 10 NAILS WITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC 10 NAILS WITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC 10 NOT THE STAKE.	RS-2 Urban Drainage and Flood O Urban Storm Drainage Criteria Stockpile Management (SP)
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION 1 LEAST SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION 1 LEAST SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW ROOM FOR SUDING SULT FENCE AT A "ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN INSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL 6 USION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN BY HAND. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN BY HAND. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN BY HAND. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN BY HAND. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCEN BY HAND. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER ON THE SHALL BE USED. A UNIFORM 6" X 4" ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. DOMPACTION SHALL BE SUCH THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR RENCH BY HAND. A SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD EN NONTCEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. A SILT FENCE SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES BY NAILS WITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABBRIC	RS-2 Urban Drainage and Flood C Urban Storm Drainage Criteria Stockpile Management (SP)
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION I LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW ROOM FOR UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW ROOM FOR UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCE MUSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL 6. SOMPACT ANCHOR TRENCH BY HAND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. 5. SILT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD 6. MONACTION SHALL BE SUCH THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR 8. SILT FENCE FARING SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 6. NO NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 8. NAILS WITH 1" HEADS, STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC 1. NOTICEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THE SHOULD BE OF SUFFICIENT LERGITH TO KEEP 1. NOTICEABLE SHALL BE INST	RS-2 Urban Drainage and Flood O Urban Storm Drainage Criteria Stockpile Management (SP)
Urban Storm Drainage Criteria Manual Volume 3 Sitt Fence (SF) ALL FENCE INSTALLATION NOTES ALL FENCE INSTALLATION NOTES ALL FENCE INSTALLATION NOTES ALL FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER NONDING, SILT FENCE, ATTHE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION T LEAST SEVERAL FEET (2–5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER NONDING AND DEPOSITION. A UNFORM STATUS AND AND AND THE TOE OF THE SLOPE TO ALLOW FOR WATER SLOPE STALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL A UNFORM STATUS AND AND AND WITH A "JUMPING JACK" OR BY WHEEL ROLLING. (DOMPACTION SHALL BE SUCH THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR RENCH BY HAND. A SLIT FENCE FABRIC SHALL BE ANGHORED TO THE STAKES, THERE SHOULD IS NUT FEAST SALL BE PULLED TIGHT AS IT IS ANGHORED TO THE STAKES, THERE SHOULD IS NUT FEAST SHALL BE ANGHORED TO THE STAKES USING 1" HEAVY DUTY STAFLES IN NAILS WITH 1" HEADS, STAFLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRE. A SILT FENCE FABRIC SHALL BE ANGHORED TO THE STAKES USING 1" HEAVY DUTY STAFLES IN NAILS WITH 1" HEADS, STAFLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRE. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE UNIXEL WITH 1" HEADS, STAFLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRE. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE UNIXE HEATS. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE UNIXE HEATS. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE UNIXE HEATS. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE A SILT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTUREING ACTIVITES. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD BE A SILT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTUREING ACTIVITES. A THE END OF A RUN OF SILT FENCE HAD OF THE SILT FENCE (MYEICALLY 10' - 20). A THE END OF A RUN OF SILT FENCE TO ANY LAND DISTUREING	
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES ALL FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EXCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHORE, OR SIMILAR EQUIPMENT SHALL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EXCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHORE, OR SIMILAR EQUIPMENT SHALL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EXCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHORE, OR SIMILAR EQUIPMENT SHALL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILL E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILLE E USED. A UNIFORM 6 [*] X 4 [*] ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER TO THE STAKES. A UNIFOR SHALL BE SUCH THAT SILT FENCE ACONG A CONTOUR, OR THE STAKES. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD RE ENDED DEPENDICULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEEP UNIFOT FRAME. A THE END OF A RUN OF SILT FENCE ALONG A CONTOUR, THE SILT FENCE SHOULD RE ENDED DEPENDICULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEEP UNIFOT FRAME. A THE END OF A RUN OF SIL	
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER NORMONG. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING. SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING AND DEPOSITION. 1. A UNIFORM 6° X 4° ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENGE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL 3. SLIT FENCE SHALL BE PULLED THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR IN NOTICEABLE AGE BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. THERE SHOULD 4. NOTICEABLE AGE BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. 5. SLIT FENCE SHALL BE ANCHORED TO THE STAKES USING 1° HEAVY DUTY STAPLES IN NOTICEABLE AGE BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES. 5. SLIT FENCE SHALL BE ANCHORED TO THE STAKES USING 1° HEAVY DUTY STAPLES IN NOTICEABLE. AGE DEVICEND TO THE STAKES USING 1° HEAVY DUTY STAPLES IN NOTICEABLE. AGE DEVICEND TO THE STAKES USING 1° HEAVY DUTY STAPLES IN NOTICEABLE. AGE ONTO NOTICE TO ANY LAND DISTURBING ACTIVITE IN STAKES SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITE IN STAKES SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITE ON THE STAKES. 1. THERCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITE IN STAKES SUBJICA AND FROMING ACQUING THE END OF THE SLIT FENCE (NISPECT BUMPS AS SOON AS SUSSICI, AND DIFFORM HEAVED. 1. SPECT BUMPS FACH WORKBAY AND MANTIANT THEM IN EFFECTIVE OPERATION CONDITION, SANDING AS STORM THAT CAUSES SURFACE. 3. SUSSICI AND DIFFORMING AND AND AND THEAVANCE, ARE NECESSARY TO MAINTAIN BUMPS IN SOON AS SUS	
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES ALL FENCE INSTALLATION NOTES SILT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION I LEAST SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION I LEAST SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING, SILT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION COMMON AND DEPOSITION A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCAVATED USING TRENCHER OR SILT ENCE INSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL E USED SLIT FENCE SHALL BE VULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD E HON ONTECEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES SLIT FENCE FABRIC SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES IN NALL SWITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC UNOT THE ISTALL BE VULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD E NO NOTECEABLE SAG BETWEEN STAKES AFTER IT HAS BEEN ANCHORED TO THE STAKES SLIT FENCE FABRIC SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES IN NAILS WITH 1" HEADS. STAPLES AND NAILS SHOULD BE PLACED 3" ALONG THE FABRIC UNOT THE ISTALLE DE VILLED TIGHT AS IT IS FENCE (VIPICALLY 10' L 20') SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIMITE SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIMITE SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIMITE SLIT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIMITE SLIT FENCE MINTERANCE AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION SUBJEL (AND ALAWYS WITHIN 24 HOURS) SPOLLO MED STORM THAT CAUSES SURFAGE SPECTE BUMPES AND MAINTAIN THEM IN THEFFECTIVE OPERATING CONDITION SUBJELE (AND ALAWYS WITHIN' 24 HOURS) STORM THAT CAUSES SURFAGE SP	
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION NOTES A ULT FENCE INSTALLATION NOTES SULT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ONDING SULT FENCE AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION COMMING SULT FENCE, AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION COMMING SULT FENCE, AT THE TOE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION COMMING AND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SULT EXCENSIONATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SMILAR COMMING TO MAGE COMMING AND DEPOSITION. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SULT EXCENSIONATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SMILAR COMMING. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SULT EXCENSIONATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SMILAR COMMING. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SULT EXCENSIONATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SMILAR COMMING. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SULT EXCENSIONATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SMILAR COMMING. A UNIFORM 6" X 4" ANCHOR TRENCH SHALL BE EXCANATED USING THE STAKES. THERE SHOULD EXCENSIONATION DEVICE. NO ROAD GRADERS USING 1" HEAVY DUTY STAPLES IN ANAL WIT 1" HEAVS. STALLES AND NAINES SHOULD BE ENACED 1" HEAVY DUTY STAPLES IN ANAL WIT 1" HEAVS. STALLES AND NAINES SHOULD BE ENACED 1" HEAVY DUTY STAPLES IN ANAL WIT 1" HEAVS. STALLES AND NAINES SHOULD BE ENACED 1" HEAVY DUTY STAPLES IN ANAL WIT 1" HEAVS. STALLES AND NAINES SHOULD BE ENACED 1" HEAVY DUTY STAPLES IN ANAL WIT 1" HEAVS. THE CONDUR TO CREATE A "U-HOOK". THE 'U-HOOK'''''''''''''''''''''''''''''''''''	<page-header> 85-3 Description of the store o</page-header>
Urban Storm Drainage Criteria Manual Volume 3 SILT FENCE INSTALLATION MOTES ALL FENCE INSTALLATION MOTES SILT FENCE AT THE ORE OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING, SILT FENCE AT THE TOP OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING, SILT FENCE AT THE TOP OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING, SILT FENCE AT THE TOP OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING, SILT FENCE AT THE TOP OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING, SILT FENCE AT THE TOP OF A SLOPE SHOULD BE INSTALLED IN A FLAT LOCATION ONDING AND DEPOSITION A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT ENCE INSTALLTON DEVICE. NO ROAD GRADERS, BACKMARE QUIPMENT SHALL EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT ENCE INSTALLTON DEVICE. NO ROAD GRADERS, BACKMARE OR SING THE SHALES A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE A UNFORM 6" X' ANCHOR TRENCH SHALL BE EXCANATED USING TRENCHER OR SILT EVELSE SULT FENCE SHALL BE PULLED TIGHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD EVENDING PERPENDICULAR TO THE CONTOUR TO CREATE A "U-HOOK" THE "U-HOOK" THE STAKES SILT FENCE SHALL BE ANCHORED TO THE STAKES USING 1" HEAVY DUTY STAPLES . THE STAKE SULT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITES SULT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITES SULT FENCE SHALL BE INSTALLED PRIOR TO ANY LAND DISTURBING ACTIVITES SULT FENCE SHALL BE INSTALLED PRIOR ON TREACTIVE. INSPECT BARPA AS SOON AS OSSIBLE (AND AND VERSION AND SATION THAT CAUSES SURFACE INFERCIT MERPENDINGULAR TO THE ORITOR AND CORRECTIVE MARASURES SHOUL	<section-header><page-header> S23 Stockpile Management (SP) <t< td=""></t<></page-header></section-header>
Distant Brown Drainage Criteria Manual Volume 3 SILF EPRCE (SFF) I. SULF FENCE INSTALLATION MOTE U , SULF FENCE INSTALLED U , SULF FENCE U , SULF	<text><section-header></section-header></text>
Urban Storm Drainage Criteria Manual Volume 3 SILT Ence (SFF) IL FENCE INSTALLATION NOTES INSTALLATION PROTECTION THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT FENCE MUST BE PLACED AWAY FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR WATER ORDING SUIT SEVERAL FEET (2-5 FT) FROM THE TOE OF THE SLOPE TO ALLOW FOR SUIT ENCE MSTALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL EVEL WATALLATION DEVICE. NO ROAD GRADERS, BACKHOES, OR SIMILAR EQUIPMENT SHALL EVEL SUED COMPACT ANCHOR TERNCH BY HAND WITH A "JUMPING JACK" OR EY WHEEL ROLLING, . SUED FERRENDEL SAME SUGH THAT SILT FENCE RESISTS BEING PULLED OUT OF ANCHOR ENCH BY HAND SUET FENCE SHALL BE PULLED TOHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD EN NORTERBEL SAM BE PULLED TOHT AS IT IS ANCHORED TO THE STAKES. THERE SHOULD INFORMED FERRENDELLAR TO THE CONTOUR SHOULD BE PLACED 3" ALCOM THE FABRIC INFORMED FERRENDELLAR TO THE CONTOUR SHOULD BE PLACED 3" ALCOM THE FABRIC INFORMEDULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEED INFORMEDULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEED INFORMEDULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEED INFORMEDULAR TO THE CONTOUR SHOULD BE OF SUFFICIENT LENGTH TO KEED INFORMEDULAR TO THE CONTOUR SHOULD BE DREACED TO THE STAKES. INFORMED FERRENDULAR TO THE CONTOUR SHOULD BE INTERIOR ACTIVITE INFORME FERRENDULAR TO THE CONTOUR SHOULD BE INTERION ACTIVITE INFORMED FERRENDULAR TO THE CONTOUR SHOULD BE INTERION ACTIVITE INFORMED FERRENDULAR TO THE CONTOUR SHOULD BE INTERION TO ANTIVITY OF THE SILT FERCE HARD SHOULD BE INTERION AND ANTIVITY INFORULY STAFLES	

SF-4

Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3 November 2010

Rock Sock (RS)



Rock Sock (RS)

ROCK SOCK MAINTENANCE NOTES

1. INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.

2. FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.

3. WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.

4. ROCK SOCKS SHALL BE REPLACED IF THEY BECOME HEAVILY SOILED, OR DAMAGED BEYOND REPAIR.

5. SEDIMENT ACCUMULATED UPSTREAM OF ROCK SOCKS SHALL BE REMOVED AS NEEDED TO MAINTAIN FUNCTIONALITY OF THE BMP, TYPICALLY WHEN DEPTH OF ACCUMULATED SEDIMENTS IS APPROXIMATELY ½ OF THE HEIGHT OF THE ROCK SOCK.

6. ROCK SOCKS ARE TO REMAIN IN PLACE UNTIL THE UPSTREAM DISTURBED AREA IS STABILIZED AND APPROVED BY THE LOCAL JURISDICTION.

7. WHEN ROCK SOCKS ARE REMOVED, ALL DISTURBED AREAS SHALL BE COVERED WITH TOPSOIL, SEEDED AND MULCHED OR OTHERWISE STABILIZED AS APPROVED BY LOCAL

(DETAIL ADAPTED FROM TOWN OF PARKER, COLORADO AND CITY OF AURORA, COLORADO, NOT AVAILABLE IN AUTOCAD) NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.

NOTE: THE DETAILS INCLUDED WITH THIS FACT SHEET SHOW COMMONLY USED, CONVENTIONAL METHODS OF ROCK SOCK INSTALLATION IN THE DENVER METROPOLITAN AREA. THERE ARE MANY OTHER SIMILAR PROPRIETARY PRODUCTS ON THE MARKET. UDFCD NEITHER NDORSES NOR DISCOURAGES USE OF PROPRIETARY PROTECTION PRODUCTS; HOWEVER, IN THE EVENT PROPRIETARY METHODS ARE USED, THE APPROPRIATE DETAIL FROM THE MANUFACTURER MUST BE INCLUDED IN THE SWMP AND THE BMP MUST BE INSTALLED AND MAINTAINED AS SHOWN IN THE MANUFACTURER'S DETAILS.

November 2010 Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3 RS-3

ment (SP) SP - 3.0' MIN STOCKPILE SILT FENCE (SEE SF DETAIL FOR INSTALLATION REQUIREMENTS) OCKPILE PROTECTION PLAN SILT FENCE (SEE SF DETAIL FOR INSTALLATION REQUIREMENTS) SECTION A 1. STOCKPILE PROTECTION NSTALLATION NOTES CKPILES. LE PROTECTION. ONTROLS IN ACCORDANCE WITH THEIR RESPECTIVE DESIGN DETAILS THE STOCKPILE PROTECTION DETAILS; HOWEVER, OTHER TYPES OF CLUDING SEDIMENT CONTROL LOGS OR ROCK SOCKS MAY BE JMSTANCES, CONSIDERATIONS FOR DETERMINING THE APPROPRIATE NTROL FOR A STOCKPILE INCLUDE WHETHER THE STOCKPILE IS S OR IMPERVIOUS SURFACE, THE RELATIVE HEIGHTS OF THE D STOCKPILE, THE ABILITY OF THE PERIMETER CONTROL TO CONTAIN FAILING IN THE EVENT THAT MATERIAL FROM THE STOCKPILE SHIFTS PERIMETER, AND OTHER FACTORS. PILE SURFACE WITH SURFACE ROUGHENING, TEMPORARY SEEDING AND TROL BLANKETS, OR SOIL BINDERS. SOILS STOCKPILED FOR AN ALLY FOR MORE THAN 60 DAYS) SHOULD BE SEEDED AND MULCHED SS COVER ONCE THE STOCKPILE IS PLACED (TYPICALLY WITHIN 14 ONLY OR A SOIL BINDER IS ACCEPTABLE IF THE STOCKPILE WILL BE IMITED TIME PERIOD (TYPICALLY 30-60 DAYS).

XPILES ON THE INTERIOR PORTION OF A CONSTRUCTION SITE, WHERE DNTROLS, INCLUDING PERIMETER CONTROL, ARE IN PLACE, STOCKPILE Y NOT BE REQUIRED.

MM-2

November 2010

MM-2

Stockpile Management (SM)

STOCKPILE PROTECTION MAINTENANCE NOTES


- 1. INSPECT BMPs EACH WORKDAY, AND MAINTAIN THEM IN EFFECTIVE OPERATING CONDITION. MAINTENANCE OF BMPs SHOULD BE PROACTIVE, NOT REACTIVE. INSPECT BMPs AS SOON AS POSSIBLE (AND ALWAYS WITHIN 24 HOURS) FOLLOWING A STORM THAT CAUSES SURFACE EROSION, AND PERFORM NECESSARY MAINTENANCE.
- 2. FREQUENT OBSERVATIONS AND MAINTENANCE ARE NECESSARY TO MAINTAIN BMPs IN EFFECTIVE OPERATING CONDITION. INSPECTIONS AND CORRECTIVE MEASURES SHOULD BE DOCUMENTED THOROUGHLY.
- 3. WHERE BMPs HAVE FAILED, REPAIR OR REPLACEMENT SHOULD BE INITIATED UPON DISCOVERY OF THE FAILURE.
- STOCKPILE PROTECTION MAINTENANCE NOTES 4. IF PERIMETER PROTECTION MUST BE MOVED TO ACCESS SOIL STOCKPILE, REPLACE PERIMETER CONTROLS BY THE END OF THE WORKDAY.
- 5. STOCKPILE PERIMETER CONTROLS CAN BE REMOVED ONCE ALL THE MATERIAL FROM THE STOCKPILE HAS BEEN USED.

(DETAILS ADAPTED FROM PARKER, COLORADO, NOT AVAILABLE IN AUTOCAD)

NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.

SP-3

SP-4



Stabilized Staging Area (SSA)




(DETAILS ADAPTED FROM DOUGLAS COUNTY, COLORADO, NOT AVAILABLE IN AUTOCAD)


5. STABILIZED STAGING AREA SHALL BE ENLARGED IF NECESSARY TO CONTAIN PARKING, STORAGE, AND UNLOADING/LOADING OPERATIONS.

6. THE STABILIZED STAGING AREA SHALL BE REMOVED AT THE END OF CONSTRUCTION. THE GRANULAR MATERIAL SHALL BE REMOVED OR, IF APPROVED BY THE LOCAL JURISDICTION, USED ON SITE, AND THE AREA COVERED WITH TOPSOIL, SEEDED AND MULCHED OR OTHERWISE STABILIZED IN A MANNER APPROVED BY LOCAL JURISDICTION.

NOTE: MANY MUNICIPALITIES PROHIBIT THE USE OF RECYCLED CONCRETE AS GRANULAR MATERIAL FOR STABILIZED STAGING AREAS DUE TO DIFFICULTIES WITH RE-ESTABLISHMENT OF VEGETATION IN AREAS WHERE RECYCLED CONCRETE WAS PLACED.

NOTE: MANY JURISDICTIONS HAVE BMP DETAILS THAT VARY FROM UDFCD STANDARD DETAILS. CONSULT WITH LOCAL JURISDICTIONS AS TO WHICH DETAIL SHOULD BE USED WHEN DIFFERENCES ARE NOTED.







SSA-4

Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3 November 2010

November 2010

VTC-1. AGGREGATE VEHICLE TRACKING CONTROL


Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3 VTC-3


VTC-6

Urban Drainage and Flood Control District Urban Storm Drainage Criteria Manual Volume 3 November 2010

	General Seed Mixes for	or Weld County
Sandy Site Mix		
Sand Bluestem	(Champ, Chet)	1.00 lbs pls/acr
Sand Lovegrass	(Bend, Native, Ne27)	2.50 lbs pls/acr
Indian Ricegrass	(Nezpar, Rimrock)	3.00 lbs pls/acr
Prairie Sandreed	(Goshen)	0.75 lbs pls/acr
Green Needlegrass	(Lodorm)	1.50 lbs pls/acr
Little bluestem	(Blaze, Cimarron, Camper)	0.75 lbs pls/acr
Yellow Indiangrass	(Cheyenne, Holt, Scout)	0.50 lbs pls/acr
Switchgrass (Black	well, Nebraska 28)	1.50 lbs pls/acr
Sand Dropseed		0.50 lbs pls/asr
	Total:	12.00 pounds pls/acre
	Total:	12.00 pounds pls/acro
<u>Wetter Site Mix</u>	Total:	12.00 pounds pls/acro
	Total: (Arriba, Barton, Rosana)	
	(Arriba, Barton, Rosana)	3.00 lbs pls/acr
Western wheatgrass Slender wheatgrass	(Arriba, Barton, Rosana)	3.00 lbs pls/acr 2.00 lbs pls/acr
Western wheatgrass Slender wheatgrass	(Arriba, Barton, Rosana) (Pryor, San Luis) II, Salt on Sea)	3.00 lbs pls/acr 2.00 lbs pls/acr 2.50 lbs pls/acr
Western wheatgrass Slender wheatgrass Alkaligrass (Fults Streambank Wheatg	(Arriba, Barton, Rosana) (Pryor, San Luis) II, Salt on Sea)	3.00 lbs pls/acr 2.00 lbs pls/acr 2.50 lbs pls/acr 2.50 lbs pls/acr
Western wheatgrass Slender wheatgrass Alkaligrass (Fults Streambank Wheatg	(Arriba, Barton, Rosana) (Pryor, San Luis) II, Salt on Sea) rass (Sodar)	12.00 pounds pls/acr 3.00 lbs pls/acr 2.00 lbs pls/acr 2.50 lbs pls/acr 2.50 lbs pls/acr 1.75 lbs pls/acr 0.50 lbs pls/acr
Western wheatgrass Slender wheatgrass Alkaligrass (Fults Streambank Wheatg Switchgrass (Nebr	(Arriba, Barton, Rosana) (Pryor, San Luis) II, Salt on Sea) rass (Sodar) aska 28, Blackwell) (Lodorm)	3.00 lbs pls/acr 2.00 lbs pls/acr 2.50 lbs pls/acr 2.50 lbs pls/acr 1.75 lbs pls/acr
Western wheatgrass Slender wheatgrass Alkaligrass (Fults Streambank Wheatg Switchgrass (Nebr Green Needlegrass Sideoats Grama (But	(Arriba, Barton, Rosana) (Pryor, San Luis) II, Salt on Sea) rass (Sodar) aska 28, Blackwell) (Lodorm)	3.00 lbs pls/acr 2.00 lbs pls/acr 2.50 lbs pls/acr 2.50 lbs pls/acr 1.75 lbs pls/acr 0.50 lbs pls/acr

Total: 14.00 pounds pls/acre






DIMENSIONS ARE FOR REFERENCE ONLY ACTUAL DIMENSIONS MAY VARY


DIMENSIONS ARE IN INCHES


JUSTICE, 28 CFR PART 36.


GRATE HAS LIGHT DUTY RATING



CD01











CD02


3490-Cover, Notes, & Details.d SHEET 62 OF 64











8" WALL (TYP.)—►

♣ A 2 IN. DIAMETER TEMPORARY

HOLE FOR DRAINAGE SHALL BE PLACED AT SUBGRADE

BE PLACED AT SUBGRADE ELEVATION OR A MINIMUM THREE INCHES BELOW ROAD BASE. THE HOLE SHALL BE PLUGGED WITH CONCRETE BEFORE ACCEPTANCE OF THE IN ET

3'-4

CURB INLE

TYPE R

Issued by the Project Development Branch: July 31, 2019

INLET.

SECTIONS C-C & D-D (DOTTED BARS ARE IN SECTION D-D)

11/4" DIA.. x 24"

3"x3"x¾" PLATE

<u>+</u> - ----- - ------- - -------

╣╇*╾╦┵*╾╦╾╾╦

JBK

GALV. STEEL ROD

1/4

2'-6" O.C.

CURB FACE ASSEMBLY

◆ PLACE ENTIRE ASSEMBLY BEFORE POURING CONCRETE.

Phone: 303-757-9021 FAX: 303-757-9868

O" EMBEDMENT

407 — 9" D.C.

8" WING F

11" O.C.

____ 406 ____ 405 6" D.C. 6" D.C.

SECTION B-B

<u>END VIEW</u>

NOTE: MANHOLE RING AND COVER, STATION POINT

AND OUTFLOW PIPE SHALL BE LOCATED AT THE SAME END OF THE INLET.

9" D.C.

2" ALL AROUND


└── 3" CLR.

STANDARD PLAN NO.

M-604-12

Standard Sheet No. 1 of 2

Project Sheet Number:



AD Ver.: MicroStation V8 Scale: Not to Scale Units:

